

(19) World Intellectual Property
Organization
International Bureau



INTERNATIONAL PATENT COOPERATION TREATY (PCT)

(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/055140 A1

(51) International Patent Classification⁷: **G06T 5/00**

(21) International Application Number:
PCT/IB2004/052518

(22) International Filing Date:
23 November 2004 (23.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03104503.2 2 December 2003 (02.12.2003) EP

(71) Applicant (for DE only): **PHILIPS INTELLECTUAL
PROPERTY & STANDARDS GMBH [DE/DE]**; Stein-
damm 94, 20099 Hamburg (DE).

(71) Applicant (for all designated States except DE, US):
KONINKLIJKE PHILIPS ELECTRONICS N. V.
[NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven
(NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MAACK,**

Hanns-Ingo [DE/DE]; c/o Philips Intellectual Prop-
erty &, Standards GmbH, Weisshausstr. 2, 52066 Aachen
(DE). **KLOESSNER, Andreas [DE/DE]**; c/o Philips
Intellectual Property &, Standards GmbH, Weisshausstr.
2, 52066 Aachen (DE).


(74) Agents: **MEYER, Michael et al.**; Philips Intellectual
Property &, Standards GmbH, Weisshausstr. 2, 52066
Aachen (DE).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: **A DEVICE AND METHOD FOR CORRECTING DEFECTS IN X-RAY IMAGES**



(57) Abstract: The invention relates to a method for correcting defects in X-ray images in which potentially defective picture elements (p) are identified in X-ray images (I), which are created during normal operation, by comparing the value (W(p)) of said picture elements with corresponding values in a neighborhood (n(p)). If a picture element (p) has been classified as "potentially defective" in more than a specified percentage of X-ray images, it is entered in a defect map which is refreshed on a continuous basis. The defect map can then be used to correct other X-ray images.